



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) Publication number:

0 566 523 A1

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 93710007.1

(51) Int. Cl. 5: **A61M 25/01**

(22) Date of filing: 02.12.88

This application was filed on 27 - 04 - 1993 as a
divisional application to the application
mentioned under INID code 60.

(30) Priority: 23.12.87 US 137963

(41) Date of publication of application:
20.10.93 Bulletin 93/42

(66) Publication number of the earlier application in
accordance with Art.76 EPC: 0 321 796

(64) Designated Contracting States:
CH DE FR GB IT LI NL

(71) Applicant: **ADVANCED CARDIOVASCULAR
SYSTEMS, INC.**
1395 Charleston Road
Mountain View, CA 94039(US)

(72) Inventor: Taylor, Charles S.
240 27th Street
San Francisco, CA 94131(US)
Inventor: Abrams, Robert M.


239 Sierra Vista
Mountain View, CA 94043(US)
Inventor: Messner, Kirsten L.
2203 Hastings Drive No.23
Belmont, CA 94022(US)
Inventor: Huss, Beverly
3500 Granada No.164
Santa Clara, California 95051(US)
Inventor: Mar, Craig E.
890 Cherry Glen Circle
Fremont, CA 94536(US)
Inventor: Kraus, Jeffrey Lloyd
1612 Babero Avenue
San Jose, CA 95118(US)
Inventor: Guthrie, Linda Theodora
4555 Thornton Avenue
Fremont, California 94536(US)

(74) Representative: Ballie, Iain Cameron et al
c/o Ladas & Parry,
Altheimer Eck 2
D-80331 München (DE)

(67) Extendable guidewire for cardiovascular procedures.

(67) An extendable guidewire system for introducing
a dilatation catheter into the cardiovascular system.
The guidewire has guidewire (12) and extension (13)
sections with a connection (18) therebetween which
permits the two sections to be joined together and

separated simply by pushing the two sections to-
gether and pulling them apart. One of the sections
can be used for positioning the catheter within the
cardiovascular system, and the other section can be
employed to extend the wire to change catheters.



Background of the Invention

This invention generally relates to cardiovascular procedures such as angioplasty, angiography and valvuloplasty, and more particularly to an extendable guidewire for use in such procedures.

Guidewires are currently used to facilitate the placement of catheters in the arterial system of a patient for cardiovascular procedures such as angioplasty, angiography and valvuloplasty. The guidewire is typically on the order of 20-50 cm longer than the catheter to permit the guidewire and the catheter to be advanced relative to each other as they are steered into position within the patient's body. Suitable guidewires are described in the U.S. Patent No. 4,538,622 (Samson et al.) and U.S. Patent No. 4,569,347 (Frisbie) which are hereby incorporated herein in their entirety.

In the usual procedure to change catheters, the guidewire is removed from the patient, and an exchange wire is inserted in its place. The in-place catheter is removed from the patient and a new catheter is inserted into the patient. The exchange wire is then removed and the guidewire is reinserted. The exchange wire is substantially longer than the guidewire, and it generally extends outside the patient's body for a distance greater than the length of the catheter. With a dilatation catheter having a length on the order of 120-140 cm, for example, a guidewire might have a length on the order of 175 cm, and an exchange wire might have a length on the order of 300 cm. The use of an exchange wire has the obvious disadvantage that it complicates the angioplasty procedure.

Heretofore, there have been some attempts to eliminate the need for a separate exchange wire by attaching an extension wire to a guidewire to extend the length thereof. The two wires are joined together by a crimped connector which requires a special tool. Once the wires have been crimped, the connection therebetween is permanent, and the extension wire cannot be removed except by severing it from the guidewire.

What has been needed and heretofore unavailable is an extension which can be readily connected and disconnected to the guidewire when it is in position within the patient. The present invention satisfies this need.

SUMMARY OF THE INVENTION

The present invention provides a new and improved guidewire system and the method of using the same.

In accordance with the present invention, a guidewire is provided with main and extension sections which are detachably secured together by press fitting. One of the guidewire sections has a

tubular portion at the connecting end thereof, and the other guidewire section has a connecting end portion which has an effective diameter in one radial dimension which is slightly larger than the inner diameter of the tubular portion. The slightly larger connecting end of one of the guidewire sections is inserted into the tubular end of the other guidewire section. One or both of the connecting ends are deformed to provide an interference or friction fit therebetween and thereby detachably secure the two guidewire sections together. The two sections can be readily separated by pulling them apart. The two sections can be reconnected and disconnected as desired.

These and other advantages of the invention will become more apparent from the following detailed description thereof and the accompanying exemplary drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a fragmentary, centerline sectional view of an extendable guidewire embodying features of the invention, with parts separated;

FIG. 2 is a fragmentary centerline view of the embodiment shown in FIG. 1 with the parts joined;

FIG. 3 is a cross-sectional view taken along lines 3-3 of FIG. 2; and

FIG. 4 is a partial centerline sectional view of an alternative embodiment.

DETAILED DESCRIPTION OF THE INVENTION

As illustrated in FIG. 1-3, the guidewire system 10 embodying features of the invention has a main section 11 which is adapted to be inserted into a patient's vascular system and an extension section 12 which can be connected and disconnected to the main section 11 to facilitate the exchange of catheters without the need for removing the main section 11 from the patient's vascular system. Main guidewire section 11 generally comprises an elongated shaft 13 with a flexible tip (not shown) at its distal end and a smaller diameter portion 14 at its proximal end which is shaped into an undulating or sinusoidal shape. Reference is made to U.S. Patent 4,538,622 (Samson et al.) and U.S. Patent 4,569,347 (Frisbie), which have been previously incorporated herein by reference, for a description of desirable guidewire tip constructions. Extension section 12 has an elongated shaft 16 with smaller diameter projection or post 17 at its distal end.

The connection 18 between guidewire sections 11 and 12 generally comprise tubular member 19 which is fixed to the distal end of the extension section 12 and which receives interfitting undulating member 14 which is on the proximal end of

main section 11. Tubular member 19 is mounted by suitable means such as welding, brazing, suturing, by an adhesive or the like onto the short axial extension 17 of reduced diameter at the distal end of shaft 16. Axial extension or post 17 can be formed by any suitable means such as grinding down the proximal end portion of the shaft 18 to the desired diameter so that it interfits into the end of tubular member 19. The undulating portion 14 is formed by first grinding the proximal end of main section 11 to a smaller diameter, then forming the undulations or sinusoidal shape by bending over a mandrel or other suitable means. The maximum effective dimension A of the undulated section should be slightly more than the inner diameter B of tubular connecting piece 19, but preferably not more than 50% greater than dimension B to provide interference or friction fit which will hold the sections together during catheter exchange but which can be readily disengaged after exchange has been made. Preferably no more than a one pound pull should be necessary for disengagement.

In a guidewire having a diameter on the order of about .36 mm (.014 inch), for example, tubular member 19 might have an inner diameter of about .18 mm (.007 inch) and a wall thickness on the order of .025 mm (.001 inch) and the undulating section 14 might have a maximum effective radial dimension of about .23 mm (.009 inch). In this embodiment, tubular member 19 might have a length on the order of about 2.4-2.5 cm.

The main guidewire section is intended for use in positioning a dilatation catheter (not shown) in the cardiovascular system of a patient, and it has a length corresponding to the length of a conventional guidewire for this purpose. Details of typical dilatation catheters and guidewires can be found in the patents cited previously and incorporated herein.

Extension section 12 is sufficiently long so that when the guidewire sections 11 and 12 are connected together the guidewire system 10 has an overall length suitable for exchanging catheters without removing the main section 11 from the patient's vascular system. With a dilatation catheter having a length on the order of 120-140 cm, for example, section 11 might have a length of 140-175 cm, and section 12 might have a length of 125-160 cm.

Shafts 13 and 16 and tubular member 19 can be fabricated from suitable material, such as stainless steel, Nitinol (55% Ni-Bal. Ti), and the like, and each should have a diameter to allow a dilatation catheter to pass freely over them. It is preferable that the two shafts 13 and 16 be of substantially the same diameter in order to provide a smooth transition between them. In one presently

preferred embodiment for use in coronary angioplasty, shafts 13 and 16 have a diameter on the order of about .36 mm (.014 inch). Either or both of the shafts can be provided with a coating of polytetrafluoroethylene, which is sold under the trademark Teflon by the DuPont Corporation, or another suitable low-friction material to facilitate the movement of the catheter over the wire.

An alternative embodiment is shown in FIG. 4 wherein the proximal end of main guidewire section 12 which is adapted to be inserted into the tubular member 19 is provided with a smaller diameter portion 30 having protrusions 31 which provide the interference or friction fit to releasably secure together the sections 11 and 12 of the guidewire system 10. The protrusions can have various shapes such as the semi-spherical shapes shown in FIG. 4, triangular shapes, or other shapes which may provide a suitable fit.

In use, the main guidewire section 11 is introduced into the vascular system of a patient with a dilatation catheter through a guiding catheter (not shown) and an introducer (not shown). When performing coronary angioplasty, the distal end of the guiding catheter is positioned in the coronary ostium, and the dilatation catheter is advanced so that it is just proximal to the tip of the guiding catheter.

The distal tip of the guidewire is advanced beyond the distal tip of the dilatation catheter while the latter is held in place. As the main guidewire section 11 is advanced, it is rotated and steered into the selected artery. The guidewire tip is preferably advanced through the lesion and beyond it, in order to permit the balloon portion of the dilatation catheter to be positioned within the lesion over a more supportive section of the guidewire. Once in position, the main guidewire section 11 is held in place and the dilatation catheter is advanced along it until the inflatable balloon thereof is within the lesion. Undulating end portion 14 remains outside the patient's body and outside any adapter which may be connected to the proximal end of the dilatation catheter.

To exchange catheters, the main guidewire section 11 is extended by manually pressing the open end of tubular member 19 on the distal end of extension section 12 onto the undulating end 14. As the tubular member 19 is inserted over the undulating end 14, either the tubular member 19 or the undulating member 14 or both deform to thereby firmly but releasably hold the two guidewire sections together. The dilatation catheter can then be withdrawn from the patient's body over the extended guidewire system.

A new dilatation catheter may then be introduced over the extension section 12 and advanced along the main guidewire section 11 within the

patient's body until the balloon crosses the lesion. Once the proximal end of the new balloon catheter has advanced beyond connection 18 and tubular end portion 19, section 12 can be removed by grasping the two guidewire sections 11 and 12 on opposite sides of the connection 18 and pulling them apart without disturbing the position of section 11 in the patient's body. As previously described, the interference or friction fit between the undulating member 14 and the tubular member 19 should be sufficiently strong to hold the two guidewire sections 11 and 12 together while dilatation catheters are being exchanged, but should be capable of separation by a pulling force less than one pound.

The invention has a number of important features and advantages. The two sections of the guidewire can be connected together whenever a longer wire is needed, and they can be separated whenever the additional length is not required. The two sections of the guidewire may be connected and disconnected by the physician by simply pressing them together and pulling them apart. This can be done as needed, and no special tools are required either to make the connection or to separate it. Thus the catheter exchange is greatly simplified.

It is apparent from the foregoing that a new and improved extended guidewire system and method of using the same have been provided. While the present invention has been described herein with the tubular connecting element fixed to the distal end of the guidewire extension section and the male member adapted to be inserted into the open end of the tubular member on the proximal end of the main guidewire section, it is obvious that the tubular element on the distal end of the extension section may be interchanged with the male member on the main guidewire section. Moreover, it will be apparent to those familiar with the art, that other modifications and improvements can be made without departing from the scope of the invention as defined by the following claims.

Claims

1. An extendable guidewire system for multiple catheter exchanges, comprising:
 - a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end adapted to extend out of the patient;
 - b. a guidewire extension section having a mating end; and
 - c. connecting means for repetitive connections between said main guidewire section and said extension section by non-permanent deformation of either of said mating

ends whereby said extension wire section and said main guidewire section can be repetitively connected and disconnected.

2. The extendable guidewire system of claim 9 wherein the maximum diameter of said connection means, after connection, is substantially the same diameter as that of said main guidewire section.
3. The extendable guidewire system of claim 9 wherein one of said mating ends is composed of elastically deformable material.
4. The extendable guidewire system of claim 9 wherein said connecting means includes a tubular member on the mating end of one of the guidewire sections, said tubular member having an open end; and a male member on the mating end of the other guidewire section.
5. The extendable guidewire system of claim 12 wherein said male member is adapted to be inserted into said open end of said tubular member.
6. The extendable guidewire system of claim 12 wherein said tubular member and said male member are releasably secured at their mating ends by frictional engagement.
7. An extendable guidewire system for multiple catheter exchanges, comprising:
 - a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end adapted to extend out of the patient;
 - b. a guidewire extension section having a mating end;
 - c. connecting means for detachably joining said mating end of said main guidewire section to said mating end of said guidewire extension section, said connecting means including a tubular member on the mating end of either said main guidewire section or said guidewire extension section, said tubular member having an open end, and a male member on the mating end of said guidewire section to which said tubular member is not connected, the male member being adapted for slidable insertion into said tubular member; and
 - d. said connecting means having a maximum diameter, after connection, no greater than the maximum diameter of said tubular member.

8. An extendable guidewire system for multiple catheter exchanges, comprising:
- a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end formed by a tubular member adapted to extend out of the patient;
 - b. a guidewire extension having a mating end;
 - c. connecting means for detachably joining said mating end of said main guidewire section to said mating end of said guidewire extension section; and
 - d. said connecting means having an overall maximum diameter, after connection, no greater than the maximum diameter of said tubular member.
9. An extendable guidewire system for multiple catheter exchanges, comprising:
- a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end adapted to extend out of the patient;
 - b. a guidewire extension having a mating end formed by a tubular member;
 - c. connecting means for detachably joining said mating end of said main guidewire section to said mating end of said guidewire extension section; and
 - d. said connecting means having an overall maximum diameter, after connection, no greater than the maximum diameter of said tubular member.
10. An extendable guidewire system for multiple catheter exchanges, comprising:
- a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end formed by a tubular member adapted to extend out of the patient;
 - b. a guidewire extension having a mating end;
 - c. connecting means for detachably joining said mating end of said main guidewire section to said mating end of said guidewire extension section; and
 - d. at least a portion of said connecting means having an overall maximum diameter, prior to connection, greater than the inside diameter of said tubular member.
11. An extendable guidewire system for multiple catheter exchanges, comprising:
- a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end adapted to extend out of the patient;
 - b. a guidewire extension having a mating end;
 - c. connecting means for repetitive connections between said main guidewire section and said extension section by non-permanent deformation of either of said mating ends whereby said mating end of said extension wire section changes length along its longitudinal axis when connected and disconnected to said main guidewire section.
12. The extendable guidewire system of claim 19 wherein one of said mating ends has a diametrical dimension larger than the inner diametrical dimension of the other said mating end so that upon insertion of one mating end into the other mating end the corresponding guidewire sections are releasably secured together.
13. An extendable guidewire system for multiple catheter exchanges, comprising:
- a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end adapted to extend out of the patient;
 - b. a guidewire extension section having a mating end; and
 - c. connecting means for repetitive connections between said main guidewire section and said extension section by non-permanent deformation of either of said mating ends whereby said mating end of said extension wire section changes length along its longitudinal axis when connected and disconnected to said main guidewire section.
14. An extendable guidewire system for multiple catheter exchanges, comprising:
- a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end adapted to extend out of the patient;
 - b. a guidewire extension section having a mating end;
 - c. connecting means for repetitive connections between said guidewire section and said extension section by the non-permanent deformation of either of said mating ends; and
 - d. means responsive to relative longitudinal movement of said connecting means for yieldably reducing the overall diameter of said mating end of said extension section.
15. The extendable guidewire system of claim 22 wherein one of said mating ends is made of
- adapted to extend out of the patient;
 - b. a guidewire extension having a mating end formed by a tubular member;
 - c. connecting means for detachably joining said mating end of said main guidewire section to said mating end of said guidewire extension section; and
 - d. at least a portion of said connecting means having an overall maximum diameter, prior to connection, greater than the inside diameter of said tubular member.

elastically deformable material.

16. An extendable guidewire system for multiple catheter exchanges, comprising:

a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end adapted to extend out of the patient;
b. a guidewire extension section having a mating end;
c. resilient, selectably releasable connecting means for repetitive connections between said main guidewire section and said extension section by the non-permanent deformation of either of said mating ends whereby said extension wire section and said main guidewire section can be repetitively connected and disconnected.

17. The extendable guidewire system of claim 24 wherein one of said mating ends is made of elastically deformable material.

18. An extendable guidewire system for multiple catheter exchanges, comprising:

a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end adapted to extend out of the patient;
b. a guidewire extension section having a mating end;
c. connecting means for repetitive connections between said main guidewire section and said extension section by non-permanent deformation of either of said mating ends; and
d. resilient spring means provided by one of said mating ends for imparting a retaining force to said other mating end after said mating ends are releasably connected.

19. An extendable guidewire system for multiple catheter exchanges, comprising:

a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end adapted to extend out of the patient;
b. a guidewire extension section having a mating end;
c. one of said mating ends adapted to receive the other mating end and to provide a detachable connection; and
d. resilient spring means within said connection for retaining said mating ends in detachable engagement.

20. A method of using an extendable guidewire system in a vascular procedure, said guidewire

system having a main guidewire section with a mating end, a guidewire extension section with a mating end, and a connection therebetween suitable for repetitive connections comprising a tubular member having an open end on one of said mating ends of the guidewire sections, a male member on the mating end of the other section which is adapted to be inserted into the open end of the tubular member and means to releasably secure the interconnected ends together, the method comprising the steps of:

a. percutaneously introducing a main guidewire section into the vascular system of a patient with the mating end thereof extending outside the body of the patient;
b. advancing a first catheter over the main guidewire section within the vascular system;
c. releasably securing the mating end of the extension guidewire section to the mating end of the main guidewire section by manually inserting the male member on one of the guidewire sections into the tubular member on the other guidewire section so that the interconnected ends are releasably secured together by a spring force between said male member and the inner surface of said tubular member;
d. withdrawing the first catheter from the vascular system of the patient over the two interconnected guidewire sections;
e. introducing a second catheter into the patient's vascular system over the two interconnected guidewire sections; and
f. disengaging the extension guidewire section from the main guidewire section by manually pulling the two guidewire sections apart with the main guidewire remaining in place in the vascular system of the patient.




21. An extendable guidewire system for multiple catheter exchanges, comprising:

a. a main guidewire section adapted to be inserted into a patient's vascular system, said guidewire section having a mating end adapted to extend out of the patient;
b. a guidewire extension having a mating end formed by a tubular member;
c. connecting means for detachably joining said mating end of said main guidewire section to said mating end of said guidewire extension section; and
d. said connecting means having an overall maximum diameter, after connection, no greater than the maximum diameter of either of said guidewire extension section or main guidewire section.

22. An extendable guidewire system comprising:
 a) a main guidewire section adapted to be inserted into a patient's vascular system which has a mating end; and
 b) a guidewire extension section having a mating end and a connection therebetween including a tubular member fixed to a mating end of one of the guidewire sections and a male member on the mating end of the other guidewire section having a maximum radial dimension slightly greater than the inner diameter of the tubular member which is adapted to be inserted into the tubular member to thereby releasably secure the two sections together.
23. The extendable guidewire system of claim 22 wherein the tubular member is fixed to the distal end of the guidewire extension section and the male member is on the proximal end of the mating guidewire section.
24. The extendable guidewire system of claim 22 wherein the tubular member is fixed to the proximal end of the guidewire section and the male member is on the distal end of the guidewire extension section.
25. The extendable guidewire system of any one of the preceding claims wherein the male member is provided with an undulated shape.
26. The extendable guidewire system of any one of the preceding claims wherein the maximum radial dimension of the male member is not more than 50% greater than the inside diameter of the tubular member.
27. The guidewire extension system of any one of the preceding claims wherein the tubular member is fixed to an end of a guidewire section by welding, brazing, suturing or by an adhesive.
28. The guidewire extension system of any one of claims 22-24 wherein the male member has protrusions on the outer surface thereof which engage the inner surface of the tubular member to thereby releasably secure the two guidewire sections together.
29. A method of using an extendable system in a vascular procedure, said guidewire having a pair of axially elongated sections with a connection at the mating ends thereof, one end of said sections comprising a tubular member and the end of the other of said sections comprising a male member having a maximum radial dimension slightly greater than the inner

diameter of the tubular member, the method comprising the steps of:

- a) introducing a main guidewire section into the vascular system of a patient with the proximal ends thereof having a male connection member remaining outside the body of the patient;
 b) advancing a first catheter along the wire section within the vascular system;
 c) detachably connecting a tubular element fixed to the distal end of an extension wire section to a male member on the proximal end of the main guidewire section by manually inserting the male end portion of the main guidewire section into the tubular member fixed to the extension section so that it grips the male member, withdrawing the first catheter from the vascular system of the patient over the two guidewire sections, introducing a second catheter into the patient's vascular system over the two wire sections; and
 d) removing the extension section by manually pulling the two guidewire sections apart to disengage the male member from the tubular member with the main guidewire section remaining in place in the vascular system of the patient.





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 93 71 0007

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl.4)
X	GB-A-2 180 454 (C.R. BARD, INC.)	7-12, 21-24, 26-27	A61M25/01
A	* page 2, line 24 - line 27; figures 2-3 *	1-6, 13-19	
	* page 3, line 71 - line 84 *		
	* abstract *		

A	US-A-4 617 715 (KOISTINEN ET AL.)	25	
	* column 1, line 25 - line 39; figure 3 *		

A	GB-A-708 884 (ELASTIC RAIL SPIKE CO. LTD.)	28	
	* figure 4 *		

			TECHNICAL FIELD SEARCHED (Int. Cl.4)
			A61M
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	
THE HAGUE		24 JUNE 1993	
		Examiner	
		MIR Y GUILLEN V.	
CATEGORY OF CITED DOCUMENTS			
T : theory or principle underlying the invention			
E : earlier patent document, not published on, or after the filing date			
U : document cited in the application			
I : document cited for other reasons			
A : technological background			
D : non-written disclosure			
P : intermediate document			
X : particularly relevant if taken alone			
Y : particularly relevant if combined with another document of the same category			
A : technological background			
D : non-written disclosure			
P : intermediate document			